



TALKPHONE



FIXED STATION ANALOG AREA OF RESCUE COMMAND UNIT FOR 5- AND 10-STATIONS

AREA OF RESCUE ASSISTANCE

THIS FULLY INTEGRATED FIXED STATION ANALOG COMMAND UNIT ACCOMMODATES UP TO 5 OR 10 ADA-COMPLIANT AREA OF RESCUE STATIONS. THE UNIT PROVIDES BOTH AUDIBLE AND VISUAL INDICATORS FOR AN INCOMING CALL—LED LIGHTS INDICATE THE CALLING LOCATION.

FEATURES

- AOR command units are fully compliant with the NFPA 72 (2016) §24.10, IBC (2018) §1009, ICC A117.1 (2017) Ch. 7, and ADAAG (2010) Ch. 7
- Automatically and continuously supervises for integrity (opens, shorts, and system ground fault), low battery backup, and 24VDC input power fail—alerts by relay output to an addressable fire panel, LED, and sounder
- Accommodates up to five (5) or ten (10) ADA-compliant area of rescue stations
- Stations receive power from command unit, powered by 24VDC
- LEDs on command unit indicate calling station and line status
- Supports up to two (2) Sub-Command Units for multiple on-site answering points
- On-site calling requires no outside phone line
- Off-site calling requires one (1) analog phone line (PSTN line)
- Solid LED indicates active call. Flashing LEDs indicate stations that are waiting to be answered. When first call is completed, second call is automatically placed and Command Unit rings. Multiple calls are placed in queue on a “first-in, first-out (FIFO)” basis.
- Built-in 24-hour battery backup in the event of primary power failure
- Includes built-in handset with volume control
- Dedicated talk/hold buttons for each area of rescue station
- Disconnect button for emergency services (i.e. connection through analog phone line/PSTN line)
- Options available for surface mounting, flush mounting, and cabinet with door

General Specifications

AOR-5 / AOR-10 COMMAND UNITS	
Construction:	16 gauge, powder coated steel
Mounting:	Flush mount with optional trim ring or surface mount
Communication:	Built-in handset with volume control receives calls—selectively originate calls using the front panel interface buttons
Power Source:	Command Unit: 24VDC, 2A (includes built-in 24-hour battery backup) Stations: Line-powered by Command Unit
Connectivity:	Supports one (1) analog phone line (PSTN line) for off-site dialing
Wiring:	One (1) twisted, shielded 18-24 AWG pair per station not to exceed 25 ohms resistance
Environment:	For indoor use
Call Station Options:	Indoor Flush Mount Model: AOR-CSE-FM Indoor Surface Mount Model: AOR-CSE-SM
Supervision Relay Outputs:	Any Call Station Activation 24VDC Input Power Fail Low Battery Backup (Low Voltage Detected) Open/Short Fault on AOR Stations System Ground Fault
Fault Reset:	Keyed switch provided for authorized personnel to temporarily silence while faults are corrected or to re-test/reset fault indicators after faults have been resolved
Warranty:	5-year limited warranty



All specifications are subject to change without notice.

ORDERING INFORMATION


Command Units

	Model Series	Station Count Support	Form Factor	Latch (only for -D form factor configuration)
	AOR	-5 Supports up to five (5) stations	[Leave Blank] Standard enclosure without door	[Leave Blank] Standard enclosure without door and latch
		-10 Supports up to ten (10) stations	-D Enclosure with door	SL Standard twist latch
				KL Keyed latch
Example #1	AOR	-5	-D	KL
Example #2	AOR	-10		

Flush Mount Trim Rings

AOR-TR10	Flush mount trim ring for AOR-5 or AOR-10 Command Unit without door
AOR-TR10-D	Flush mount trim ring for AOR-5 or AOR-10 Command Unit with door

Class 2 Power Supply for Command Unit



Sub-Command Unit



NOTE:
Maximum of two (2) Sub-Command Units supported on each system

AOR Stations

AOR-CSE-FM	AOR-CSE-NM	AOR-CSE-SM	AOR-CSE-FM-1RO	AOR-CSE-NM-1RO	AOR-CSE-SM-1RO

Analog AOR Station with EMERGENCY signage and flush mount

Analog AOR Station with EMERGENCY signage—mount not included

Analog AOR Station with EMERGENCY signage and surface mount

Analog AOR Station with EMERGENCY signage, one (1) relay output, and flush mount

Analog AOR Station with EMERGENCY signage and one (1) relay output—mount not included

Analog AOR Station with EMERGENCY signage, one (1) relay output, and surface mount


ORDERING INFORMATION (CONTINUED)

Signage

ETP-SIGN	ETP-SIGN/R	ETP-SIGN/L	ETP-SIGN/LR	ETP-SIGN/LD	ETP-SIGN/LDR	ETP-SIGN-PFH
						
"AREA OF RESCUE" sign with self-adhesive, raised lettering, and braille	"AREA OF REFUGE" sign with self-adhesive, raised lettering, and braille	"AREA OF RESCUE ASSISTANCE" sign lighted in red LEDs	Analog AOR Station with "AREA OF REFUGE" sign lighted in red LEDs	"AREA OF RESCUE ASSISTANCE" deluxe lighted sign	"AREA OF REFUGE" deluxe lighted sign	"PUSH FOR HELP" instructional sign with self-adhesive

SPECIFICATIONS


	AOR-5	AOR-10
		
Description:	Fixed station analog area of rescue command unit for up to five (5) stations	Fixed station analog area of rescue command unit for up to ten (10) stations
Dimensions (W x H x D) with Handset:	13.3 x 18.0 x 6.9 in. (337 x 457 x 174 mm)	
Dimensions (W x H x D) without Handset:	13.3 x 18.0 x 4.1 in. (337 x 457 x 105 mm)	
Dimensions With Trim Ring (W x H x D):	15.3 x 20.1 x 6.9 in. (389 x 511 x 174 mm)	
Weight:	25 lbs. (11.3 kg)	

	AOR-5-DKL or AOR-5-DSL	AOR-10-DKL or AOR-10-DSL
		
Description:	Fixed station analog area of rescue command unit with door and latch, for up to five (5) stations	Fixed station analog area of rescue command unit with door and latch, for up to ten (10) stations
Dimensions (W x H x D) with Handle:	14.6 x 19.3 x 7.6 in. (371 x 489 x 193 mm)	
Dimensions (W x H x D) without Handle:	14.6 x 19.3 x 6.5 in. (371 x 489 x 166 mm)	
Dimensions With Trim Ring (W x H x D):	16.3 x 21.1 x 7.6 in. (414 x 536 x 193 mm)	
Weight:	35 lbs. (15.9 kg)	

All specifications are subject to change without notice.


DIMENSIONAL DRAWING – MODEL AOR-5

All dimensions are in inches and are provided for reference only.



DIMENSIONAL DRAWING – MODEL AOR-10-DKL

All dimensions are in inches and are provided for reference only.



THE LEADERS IN SECURITY AND LIFE SAFETY COMMUNICATIONS

Tel: 773-539-1100
 Email: info@talkaphone.com
 Web: www.talkaphone.com

7530 North Natchez Avenue
 Niles, Illinois 60714

Terms of Use and Limited Warranty

This Product includes intellectual property and proprietary rights owned by Talk-A-Phone, LLC and/or its licensors. Your use of this Product confirms your agreement that Talk-A-Phone, LLC and/or its licensors retain all right, title and interest in and to all such property; that your rights are to access and use the Product for your internal business use only; that all Product elements will be maintained as confidential; and that the Product may not be rented, leased or lent to third parties, reverse engineered, decompiled or disassembled, or otherwise used for any purpose other than as an access device for your premises.

Talk-A-Phone, LLC warrants Talk-A-Phone Emergency Phone, Call Station, and Wide-Area Emergency Broadcast System equipment against any defects in material and workmanship, under normal use, for a period of twenty-four (24) months from date of installation, provided that Talk-A-Phone receives a completed "Installation Certification" certifying the date on which the system has been installed. An "Installation Certification" card is enclosed with every unit. In the event that no "Installation Certification" is received by Talk-A-Phone, the twenty-four (24) months will commence on the date of shipment by Talk-A-Phone. Warranty period for the metal elements of models in the GP Series Pedestals, MT Series Towers, MTE Series Towers, MT/R Series Towers, PM Series Pedestals, SM Series Surface Mounts, Via Series Mounts, and WM Series Wall Mounts is five (5) years, under the same terms and conditions. Warranty period for Area of Rescue Products is sixty (60) months, under the same terms and conditions. Warranty period for Intercommunication Products is twelve (12) months, under the same terms and conditions. If the Product is found by Talk-A-Phone to be defective within the warranty period, Talk-A-Phone's only obligation, and your exclusive remedy, is for the repair or replacement of any defective parts, provided that the Product is returned to us at 7530 N. Natchez Ave., Niles, IL 60714. Talk-A-Phone shall have no obligation to furnish or pay for the labor of any third parties or bear the expense of shipping defective Products for repair. In no event shall Talk-A-Phone or its licensors or suppliers be liable for any form of exemplary or punitive damages, or any special, indirect or consequential damages. TALK-A-PHONE EXPRESSLY DISCLAIMS ALL OTHER WARRANTIES, WHETHER EXPRESS, IMPLIED OR STATUTORY, INCLUDING BUT NOT LIMITED TO THE IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. In no event shall Talk-A-Phone or its licensors or suppliers be liable for any form of exemplary or punitive damages, or any special, indirect or consequential damages. Your use of this Product constitutes your agreement to all of the foregoing terms.

THIS WARRANTY GIVES YOU SPECIFIC LEGAL RIGHTS AND YOU MAY ALSO HAVE OTHER RIGHTS WHICH VARY FROM STATE TO STATE. Further information is available at talkaphone.com/legal
 Copyright 2022 Talk-A-Phone, LLC All Rights Reserved - Rev. 3/17/2022