



## CALL STATION ACCESSORIES

### **POE-MID-EXT-1** **Single-Port, IEEE 802.3at,** **Power over Ethernet (PoE)** **Midspan Extractor**

#### **Description**

Talkaphone's **POE-MID-EXT-1** Single-Port Power over Ethernet (PoE) Midspan Extractor is designed to provide power to an ETP-EL12/24 Blue Light, an LED Panel Light (P/N 68590), and/or VOIP-500/VOIP-600 Series IP Call Station via a 30W, IEEE 802.3at network connection.

Network connections providing 15.4W (IEEE 802.3af) can only support an ETP-EL12/24 and an LED Panel Light (P/N 68590).

#### **Features**

- Outputs 12VDC up to a maximum of 25W of power to a non-PoE device from a 30W, IEEE 802.3at PoE source
- RJ45 connectors for data input and output
- Two (2) terminal strips for DC output and power level selection
- Selectable for 13W or 25W output
- Requires an IEEE 802.3at Ethernet switch (provided by others) with ports supporting a minimum output power of 30W

#### **Specifications**

Input Voltage:	42.5 to 57VDC PoE input voltage
Input Current:	0.6A input current
Output Power:	12VDC output voltage (13W or 25W)
Data Rate:	10/100/1000BASE-T
Compliance:	UL 294B UL/CUL 60950-1 CSA C22.2 No.205-M1983, Signal Equipment RoHS
Operating Temperature:	+32°F to +120°F (0°C to +49°C)
Warranty:	2-year limited warranty